

Costing for	<b>Sample costing for offset flue</b>	Costing ref	<b>200id-8000-300-CH</b>	
House type	<b>House with 200 mm id flue</b>	Date	<b>01 Jun 2011</b>	
Drawing ref.	<b>Chimney height 8000 offset 300</b>	Liner size	<b>200 mm id round</b>	
Site	Church Lane, XY15 2YY	Lintel type	<b>Raft lintel for stove</b>	
Plot number	Plot 10	Offset	<b>Flue offset is 295mm</b>	
<b>Components</b>	<b>Product reference</b>	<b>Qty</b>	<b>Ex-works prices each cost</b>	
<b>Fireplace Recess</b>			£	£
Raft lintel for 200mm id	200CH1200	1	113.07	113.07
<b>First liner before offset</b>				
200mm flue liner 230mm tall	200L230	1	7.88	7.88
<b>Offset components</b>				
200mm flue bend 22.5 degree no straight liners in the offset	200B	1	12.86	12.86
200mm flue liner 600mm tall	200L600	1	13.17	13.17
200mm flue bend 22.5 degree	200B	1	12.86	12.86
<b>Straight flue run</b>				
200mm flue liner 600mm tall	200L600	9	13.17	118.53
200mm flue liner 150mm tall	200L150	3	6.23	18.69
<b>Jointing &amp; Infill</b>				
Flue liner sealant 310ml	Dunseal	6	4.69	28.14
Infill aggregate 22kg mix for void	Dunfil	12	11.55	138.60
<b>Other components</b>				
Stove - unspecified	Stove *			
Cannon pot 450mm tall red	Cann450R	1	31.61	31.61
Topguard cowl 260 tall red	TG260R	1	81.68	81.68
Smoke pellet tube	Smoke	1	8.22	8.22
Flue notice plate	Plates	1	5.88	5.88
<b>Carriage</b>				
Dunbrik haulage charges to UK mainland within 300 miles of works; orders over £1,365 are del				82.00
<b>Cost per flue</b>	Goods value		£	<b>673.19</b>
	VAT	@	20.0%	<b>134.64</b>
	Total		£	<b>807.83</b>

**Terms**

Charge for individually plotting multiple flue orders is £25 per flue.

Prices are based on our ex-works price list dated June 2011. Prices are valid for 60 days and are subject to VAT.

Telephone Dunbrik on 01924 373694 for details of your nearest supplier. Trading is subject to Dunbrik conditions of sale.

**Basis of costing**

**This is a sample costing for a 200 mm id round system with a raft lintel.**

The flue height is 8113mm from finished floor level to underside of pot with a flue offset of 295mm at 45 deg. rotated from the right wall.

The height of the recess is taken as 1100 mm from finished floor level to the underside of the lintel and with a 100mm hearth above FFL.

Although the flue height has been rounded up, if your lintel height is lower, more flue liners may be needed.

The Dunfil is based on a 15mm gap around the liners, i.e. a 290 mm square chimney space. Larger voids will require more infill.

The void around the flue offset should be minimised with blockwork to reduce the infill.

The hearth, recess and any stove, stove-pipe, canopy and chimney blockwork are not supplied by Dunbrik.

Please check the type of chimney pot and terminal to your requirements. Red is assumed if not specified.

**System information**

Flue design and installation guidance is available by post, fax or from the website.

Dunbrik liners have passed European standard BSEN1857 Type A1 (T600 N1 G D 3)

For stoves with flue pipe up to 200mm external diameter.

**Standard construction notes**

Please refer to the Dunbrik A1 concrete flue liners installation guide

The liners to be encased in masonry with any voids around liners infilled with Dunfil. Any internal jambs need to be 200mm solid.

Support lintel on three sides with 100mm blockwork leaving a maximum builders opening of 1,000mm and recess depth of 410mm.

The construction hearth is to have a minimum depth of 125mm.

The flue can be angled towards the desired termination position by rotating the first liner bend to offset the flue run in any direction.

**Special notes**

**A costing can be compiled to match your fire, flue size, flue offset and chimney height.**

Product brochures and installation guides are available in PDF format from the website: [www.dunbrik.co.uk](http://www.dunbrik.co.uk).

Please let us know if you require any further information.